



Description	LED linear luminaire available in various lengths, profiles and diffusers	
Materials	Manufactured from extruded aluminium	
Profile	50mm x 75mm	Downlight only (D)
	50mm x 95mm	Up/Down light (U)
	67mm x 75mm	Downlight with Trim (T)
Length	Desired length in millimetres e.g. 1500	
Cutout Dimensions	(Length + 5mm) x 55mm	
Installation	Recessed (R), Surface Mounted (SM) or Suspended (SS)	
Body Colour	Anodised, White (W) or Black (B)	
Luminous Flux per Metre	1500L (15W), 2000L (20W), 3000L (30W) or 4500L (45W)	
LED Colour Temperature	2700K, 3000K, 4000K	
Diffuser	Microprism (MP) or opal (OP)	
Accessories available	Uplight at desired Luminous Flux e.g. (UL2000) DALI dimming (DD) Q-Sense (QS), Microwave (MW) or other sensors available 3 hour emergency (EM3), DALI emergency (EMD) or self-test emergency (EMST)	

Product Code

PRODUCT / PROFILE / LENGTH / INSTALLATION/ BODY COLOUR / FLUX / LED COLOUR / DIFFUSER / ACCESSORIES

Example: **LIN50/U/1500/SS/B/3000L/4000K/OP/UL2000**

= LINTEQ 50, Up/Down profile, 1500mm length, suspended, black finish, 3000lm/metre downlight, 4000K, opal diffuser, 2000lm/metre uplight

EDGE LIGHTING SERVICES LTD

Unit 1, Abbey Industrial Estate, 24 Willow Lane, Mitcham, Surrey CR4 4NA
020 8687 0190 sales@edgelighting.co.uk edgelighting.co.uk