



Description	Recessed LED bi-axial gimble adjustable spotlight
Materials	Manufactured from cast aluminium
Installation	Suitable for use in all ceiling types up to a thickness of 20mm using spring clips supplied
Body Colour	White (W) , Black (B) or Silver (S)
Body Dimensions	336mm x 336mm x 240mm
Cutout Dimensions	325mm x 325mm
Tilt / Rotation	Biaxial tilting 0-40°
Luminous Flux	4x1500L (52W), 4x2000L (68W) 4x3000L (100W) or 4x4500L (148W)
LED Colour Temperature	3000K or 4000K
Beam Angle	Narrow beam (NB) , Medium beam (MB) or Wide beam (WB)
Accessories available	Lead & plug DALI dimming (DD)

Product Code

PRODUCT / BODY COLOUR / FLUX / LED COLOUR / BEAM / ACCESSORIES

Example: **GIM.QUAD/W/4x2000L/4000K/NB**

= GIMTEQ QUAD, white body, 8000 lumens, 4000K, narrow beam

EDGE LIGHTING SERVICES LTD

Unit 1, Abbey Industrial Estate, 24 Willow Lane, Mitcham, Surrey CR4 4NA
020 8687 0190 sales@edgelighting.co.uk edgelighting.co.uk