



|                        |  |
|------------------------|--|
| Description            | Lay-in modular three-aperture LED luminaire suitable for retail applications   |
| Materials              | Manufactured from mild steel with prismatic diffuser   |
| Installation           | 600mm exposed grid   |
| Body Colour            | White  |
| Body Dimensions        | 596mm x 596mm x 65mm   |
| Luminous Flux          | <b>6000L</b> (49W) or <b>8000L</b> (67W)   |
| LED Colour Temperature | <b>3000K</b> or <b>4000K</b>   |
| Accessories available  | Lead & plug<br>3 hour emergency ( <b>EM3</b> ), DALI emergency ( <b>EMD</b> ) or self-test emergency ( <b>EMST</b> )<br>DALI dimming ( <b>DD</b> )<br>Q-Sense ( <b>QS</b> ) or other sensors |

## Product Code

PRODUCT / FLUX / LED COLOUR / ACCESSORIES

Example: **TRI/6000L/4000K**

= TRITEQ, 6000 lumens, 4000K

## EDGE LIGHTING SERVICES LTD

Unit 1, Abbey Industrial Estate, 24 Willow Lane, Mitcham, Surrey CR4 4NA  
020 8687 0190 [sales@edgelighting.co.uk](mailto:sales@edgelighting.co.uk) [edgelighting.co.uk](http://edgelighting.co.uk)