



Description	Linear reeded opal LED luminaire
Materials	Manufactured from aluminium with prismatic polycarbonate diffuser and end caps
Body Dimensions	1190mm x 210mm x 68mm (1200) 1490mm x 210mm x 68mm (1500)
Installation	Surface Mounted (SM) or Suspended (SS)
Body Colour	White
Luminous Flux	1200mm: 3000L (25W), 4500L (37W) or 6000L (52W) 1500mm: 4500L (37W), 5500L (46W), 6500L (55W) or 7500L (64W)
LED Colour Temperature	3000K or 4000K
Accessories available	3 hour emergency (EM3), DALI emergency (EMD) or self-test emergency (EMST) 1-10v dimming (D10) or DALI dimming (DD) Sensors or corridor function (CF)

Product Code

PRODUCT / DIMENSIONS / INSTALLATION / FLUX / LED COLOUR / ACCESSORIES

Example: **EDU.1200/SM/3000L/4000K**

= EDUTEQ 1190mm, surface mounted, 3000 lumens, 4000K

EDGE LIGHTING SERVICES LTD

Unit 1, Abbey Industrial Estate, 24 Willow Lane, Mitcham, Surrey CR4 4NA
020 8687 0190 sales@edgelighting.co.uk edgelighting.co.uk