



Description	Recessed LED bi-axial gimble adjustable spotlight
Materials	Manufactured from cast aluminium
Installation	Suitable for use in all ceiling types up to a thickness of 20mm using spring clips supplied
Body Colour	White ( <b>W</b> ), Black ( <b>B</b> ) or Silver ( <b>S</b> )
Body Dimensions	336mm x 178mm x 120mm
Cutout Dimensions	325mm x 170mm
Tilt / Rotation	Biaxial tilting 0-40°
Luminous Flux	<b>2x1500L</b> (26W), <b>2x2000L</b> (34W) <b>2x3000L</b> (50W) or <b>2x4500L</b> (74W)
LED Colour Temperature	<b>3000K</b> or <b>4000K</b>
Beam Angle	Narrow beam ( <b>NB</b> ), Medium beam ( <b>MB</b> ) or Wide beam ( <b>WB</b> )
Accessories available	Lead & plug DALI dimming ( <b>DD</b> )

### Product Code

PRODUCT / BODY COLOUR / FLUX / LED COLOUR / BEAM / ACCESSORIES

Example: **GIMDUO/W/2x1500L/4000K/NB**

= GIMTEQ DUO, white body, 3000 lumens, 4000K, narrow beam

### EDGE LIGHTING SERVICES LTD

Unit 1, Abbey Industrial Estate, 24 Willow Lane, Mitcham, Surrey CR4 4NA  
020 8687 0190 sales@edgelighting.co.uk edgelighting.co.uk