



IP65 suitable for exterior use but limited to under canopies and sheltered areas. Not for installation in direct sunlight, open areas, exposed walls. For adverse conditions see Stormteq range.



Description	Surface mounted LED IP65 linear luminaire supplied with integral control gear
Materials	Manufactured from high-impact resistant polycarbonate
Body Colour	Grey
Body Dimensions	600: 665mm x 134mm x 98mm 1200: 1275mm x 134mm x 98mm 1500: 1575mm x 134mm x 98mm
Luminous Flux	600: 1500L (12W), 2000L (17W) or 2500L (22W) 1200: 3000L (23W), 4000L (32W) or 5000L (41W) 1500: 3000L (22W), 4000L (30W), 5000L (39W), 6000L (48W) or 8000L (75W)
LED Colour Temperature	3000K or 4000K
Accessories available	Suspensions (SS) 3 hour emergency (EM3), DALI emergency (EMD) or self-test emergency (EMST) 1-10v dimming (D10) or DALI dimming (DD) Low smoke and fume internal wiring (LSF), Metal mounting clips (MC) Sensors

Product Code

PRODUCT / DIMENSIONS / FLUX / LED COLOUR / ACCESSORIES

Example: **TOUGH.1200/4000L/4000K**

= TOUGHTTEQ 1275mm length, 4000 lumens, 4000K

EDGE LIGHTING SERVICES LTD

Unit 1, Abbey Industrial Estate, 24 Willow Lane, Mitcham, Surrey CR4 4NA
020 8687 0190 sales@edgelighting.co.uk edgelighting.co.uk