



Description	IP66 LED luminaire with various light distribution and output options
Materials	Manufactured from cast aluminium with tempered glass
Body Colour	Black
Body Dimensions	MINI: 299mm x 240mm x 92mm MIDI: 381mm x 340mm x 92mm MAXI: 559mm x 400mm x 102mm
Installation	Wall Mounting Bracket (WMB) Pole Mounting Coupler (PMC)
Light Distribution	Asymmetric Forward (AF), Asymmetric Wide (AW) or Open Area (OA)
Luminous Flux	MINI: 2600L (22W) or 4500L (43W) MIDI: 9500L (87W) or 14000L (120W) MAXI: 21500L (177W) or 33500L (281W)
LED Colour Temperature	4000K or 5000K
Accessories available	Photocell (PC)

Product Code

PRODUCT / BODY / INSTALLATION / DISTRIBUTION / FLUX / LED COLOUR / ACCESSORIES

Example: **PARQ.AREA/MIDI/PMC/AF/9500L/4000K**

= PARQ AREA MIDI, black colour, asymmetric forward throw, 9500 lumens, 4000K, pole mounting coupler

EDGE LIGHTING SERVICES LTD

Unit 1, Abbey Industrial Estate, 24 Willow Lane, Mitcham, Surrey CR4 4NA
020 8687 0190 sales@edgelighting.co.uk edgelighting.co.uk