



Description	Surface mounted LED IP65 linear luminaire supplied with integral control gear
Materials	Manufactured from high-impact resistant polycarbonate
Body Colour	Grey
Body Dimensions	<b>1200:</b> 1190mm x 95mm x 75mm <b>1500:</b> 1490mm x 95mm x 75mm <b>1800:</b> 1790mm x 95mm x 75mm
Luminous Flux	1200: <b>2500L</b> (20W) or <b>5000L</b> (38W) 1500: <b>3000L</b> (30W) <b>6000L</b> or <b>8000L</b> (60W)
LED Colour Temperature	<b>4000K</b>
Accessories available	3 hour emergency ( <b>EM3</b> ), DALI emergency ( <b>EMD</b> ) or self-test emergency ( <b>EMST</b> ) DALI dimming ( <b>DD</b> ) Microwave ( <b>MW</b> ) Sensors Suspension kit ( <b>SK</b> )

## Product Code

PRODUCT / DIMENSIONS / FLUX / LED COLOUR / ACCESSORIES

Example: **TOUGH1200/4000L/4000K**

= TOUGHTEQ 1275mm length, 4000 lumens, 4000K

## EDGE LIGHTING SERVICES LTD

Unit 1, Abbey Industrial Estate, 24 Willow Lane, Mitcham, Surrey CR4 4NA  
020 8687 0190 [sales@edgelighting.co.uk](mailto:sales@edgelighting.co.uk) [edgelighting.co.uk](http://edgelighting.co.uk)