



Description	Recessed LED bi-axial gimble adjustable spotlight
Materials	Manufactured from cast aluminium
Installation	Suitable for use in all ceiling types up to a thickness of 20mm using spring clips supplied
Body Colour	White ( <b>W</b> ), Black ( <b>B</b> ) or Silver ( <b>S</b> )
Body Dimensions	Ø136mm x 115mm depth
Cutout Dimensions	Ø126mm
Tilt / Rotation	Biaxial tilting 0-40°
Luminous Flux	<b>1500L</b> (13W), <b>2000L</b> (17W) or <b>3000L</b> (25W)
LED Colour Temperature	<b>3000K</b> or <b>4000K</b>
Beam Angle	Narrow beam ( <b>NB</b> ), Medium beam ( <b>MB</b> ) or Wide beam ( <b>WB</b> )
Accessories available	Lead & plug 1-10v dimming ( <b>D10</b> ) or DALI dimming ( <b>DD</b> )

### Product Code

PRODUCT / BODY COLOUR / FLUX / LED COLOUR / BEAM / ACCESSORIES

Example: **CIR.136/W/2000L/4000K/MB**

= CIRTEQ 136mm diameter, white, 2000 lumens, 4000K, medium beam

### EDGE LIGHTING SERVICES LTD

Unit 1, Abbey Industrial Estate, 24 Willow Lane, Mitcham, Surrey CR4 4NA  
020 8687 0190 sales@edgelighting.co.uk edgelighting.co.uk