



# **ORBIT 600**

The Orbit is a performance feature pendant, as the ring sibling of our Linteq range. Available in various finishes, wraps and sizes, customisation is key to unlocking its potential.




















### TECHNICAL INFORMATION

Installation	Surface Mounted (SM) or Suspended (SS)
Body Colour	Grey (G), White (W) or Black (B)
Dimensions	50mm x 70mm x Ø600mm
Lumen Output	3000lm (30W), 4500lm (45W)
Colour Temperature	3000K, 4000K, 5000K or Tuneable White
Colour Rendering Index	CRI90
Optical Distribution	Direct: Opal Diffuser (OP) Direct/Indirect: Opal Diffuser (IDOP)
Ingress Protection	IP20
Controls	Fixed Output (FO), DALI (DD), Q-Sense (QS) or Casambi (CS)
Emergency	3 Hour Emergency (EM3) or DALI Emergency (EMD)

Accessories

-

#### **DIMENSIONS**



## PRODUCT SHOWCASE



## PRODUCT CODE

#### ORB600/SS/B/3000LM/4000K/90/OP/20/DD

Orbit 600, suspended, black finish, 3000 lumens per metre, 4000K, CRI90, direct: opal diffuser, IP20 rated, DALI dimming

SPECIFICATIONS MAY BE ALTERED WITHOUT ADVANCE NOTICE.





