



# **DRUMTEQ MIDI**


Our Drumteq range features triple anti-glare design in spun aluminium body for minimal fuss. This range is perfect for solid ceiling installations and is available surface mounted or suspended.



## **TECHNICAL INFORMATION**

Installation	Surface Mounted (SM) or Suspended (SS)
Body Colour	White (W) or Black (B)
Dimensions	Ø140mm x 162mm
Lumen Output	2700lm (32W)
Colour Temperature	3000K or 4000K
Colour Rendering Index	CRI90
Optical Distribution	Narrow Beam (NB) or Medium Beam (MB)
Ingress Protection	IP20
Controls	Fixed Output (FO), DALI (DD), Q-Sense (QS) or Casambi (CS)
Emergency	3 Hour Emergency (EM3) or DALI Emergency (EMD)
Accessories	-

#### DIMENSIONS





#### **PRODUCT SHOWCASE**



## PRODUCT CODE

#### DRM/MID/SM/W/2700LM/4000K/90/NB/20/DD

Drumteq Midi, surface mounted, white finish, 2700 lumens, 4000K, CRI90, narrow beam, IP20 rated, DALI dimming

in

SPECIFICATIONS MAY BE ALTERED WITHOUT ADVANCE NOTICE.



#### Contact us for more information

**\$** 020 8687 0190

